



Galaxy® G4826

Galaxy® G4826

This hose is recommended for R134a and R12 refrigerants in automotive, heavy-duty truck, construction and agricultural air conditioning systems.

Performance + Specs

Meets or exceeds the performance requirements of:

- **SAE J2064, Type C Class II**

Inner Tube

CR (Polychloroprene) Black

Reinforcement

2-Spiral Polyester

Cover

EPDM Rubber Black

Temperature Range

-22°F / -30°C ~ 257°F / 125°C

Key Features

4:1 Safety Factor

Air conditioning

Branding

Galaxy® 4826-Size 8 SAE J2064 Type C Class II 13/32" (10.3 MM)

Galaxy® G4826

Product Numbers

SAP	Product #	ID	ID	OD	Max Working Pressure		Bend Radius		MIN BURST Pressure		Fitting Type	Weight (lb/ft)		
		Fraction	in.	mm.	in.	mm.	PSI	MPa	in.	mm.	PSI	Mpa		
20290026	G4826-06	5/16	0.31	7.90	0.75	19.10	500	3.4	0.60	16.00	2000	13.80	AC	0.2
20290027	G4826-08	13/32	0.41	10.30	0.91	23.00	500	3.4	1.00	25.00	2000	13.80	AC	0.28
20290028	G4826-10	1/2	0.50	12.70	1.00	25.40	500	3.4	1.30	32.00	2000	13.80	AC	0.33
20290029	G4826-12	5/8	0.63	15.90	1.13	28.60	350	2.4	2.00	50.00	1400	9.65	AC	0.38