

Galaxy® SLE G4890

Galaxy® G4867 is recommended for R134a, refrigerant blends and compressor lubricants as a suction line in air conditioning systems for heavy-duty trucks.

Performance + Specs

Meets or exceeds the performance requirements of:

- **SAE J2064, Type C Class I**

Inner Tube

CR (Polychloroprene) Black

Reinforcement

Single-Braid Polyester

Cover

Chlorobutyl Black

Temperature Range

-40°F / -40°C ~ 275°F / 135°C

Key Features

4:1 Safety Factor

Air conditioning

Branding

Galaxy® by ContiTech 4890-Size 8 SAE J2064 Type C Class II 13/32" (10.3 MM)

Galaxy® SLE G4890

Product Numbers

SAP	Product #	ID	ID	OD	Max Working Pressure	Bend Radius	MIN BURST Pressure	Fitting Type	Weight (lb/ft)					
		Fraction	in.	mm.	in.	mm.	PSI	MPa	in.	mm.	PSI	Mpa		
20306246	G4890-06	5/16	0.31	7.90	0.56	14.70	500	3.4	1.00	25.00	2000	13.80	AC	0.09
20306247	G4890-08	13/32	0.41	10.30	0.69	17.30	500	3.4	1.50	38.00	2000	13.80	AC	0.12
20306248	G4890-10	1/2	0.50	12.70	0.75	19.40	500	3.4	2.50	63.00	2000	13.80	AC	0.13
20306249	G4890-12	5/8	0.63	15.90	0.94	23.60	350	2.4	4.00	104.00	1750	12.10	AC	0.2