

Continental **X LIFE™** **XBR7**

Continental **X LIFE™** **XBR7**



X-Life™ XBR7

XBR7 is a medium-pressure, twin-line thermoplastic hose with a non-perforated cover. It is compatible with petroleum-, water- and synthetic-based fluids for mobile equipment, lube lines, blowout preventers, hydraulic lifts and construction machinery requiring SAE 100R7 non-conductivity standards.

Performance + Specs

- SAE 100R7

Inner Tube

Polyester White

Reinforcement

1 or 2 Layers, Braided Synthetic Fibers

Cover

Polyurethane, Non Pin-Pricked Orange

Temperature Range

-40°F / -40°C ~ 212°F / 100°C

Key Features

- 4:1 Safety Factor
- Non-Conductive
- Twin-Line Hose

Branding

CONTINENTAL X-LIFE™ XBR7-04 1/4 (DN6) SAE 100R7 NON-CONDUCTIVE 3000 PSI (21.0 MPA) MSHA IC-305

X-Life™ XBR7

Product Numbers														
SAP	Product #	ID	ID		OD		Max Working Pressure		Bend Radius		MIN BURST Pressure		Fitting Type	Weight (lb/ft)
		Fraction	in.	mm.	in.	mm.	PSI	MPa	in.	mm.	PSI	Mpa		
21151350	XBR7-04	1/4	0.25	6.50	0.48	12.20	3046	21.00	1.38	35.00	12184	84.00	UC	0.17
21151351	XBR7-06	3/8	0.38	9.70	0.63	16.00	2321	16.00	2.17	55.00	9284	64.01	UC	0.19
21151352	XBR7-08	1/2	0.50	13.00	0.80	20.30	2031	14.00	2.95	75.00	8124	56.01	UC	0.2

No Fittings Found