



X-LIFE™ XCP5

X-LIFE™XCP5 is made for very high-pressure hydraulic applications requiring extra abrasion resistance, tight bends and flexibility, this constant pressure hose steps up to the task. Excellent impulse performance, Meets ISO 18752 AC.

Performance + Specs

Meets or exceeds the performance requirements of:	Inner Tube Nitrile (NBR) Black
- ISO 18752 AC - Meets Flame Resistance - USMSHA Designation - X-life™ Abrasion resistant Synthetic Rubber (Black) - Constant pressure	Reinforcement Two braids of high-tensile steel wire
	Cover Synthetic Rubber Black
	Temperature Range -40°F / -40°C ~ 212°F / 100°C

Key Features

4:1 Safety Factor
Constant Pressure
Extended Life™ Cover
Flame Resistance

Branding

Continental X-Life™ XCP5-08 ISO 18752 AC 1/2" (DN12) 5075 PSI 35.0 MPa 350BAR MSHA 2G-1C-14C/37 MADE IN USA

X-LIFE™ XCP5

Product Numbers													
SAP	Product #	ID	ID	OD		Max Working Pressure		Bend Radius		MIN BURST Pressure		Fitting Type	Weight (lb/ft)
		Fraction	in.	mm.	in.	mm.	PSI	MPa	in.	mm.	PSI	Mpa	
21190062	XCP5-04	1/4	0.26	6.00	0.54	13.72	5075	35.00	2.00	50.80	23200	160.00	B2 0.19
21190064	XCP5-06	3/8	0.33	10.00	0.70	17.98	5075	35.00	2.50	63.50	23200	160.00	B2 0.3
21190066	XCP5-08	1/2	0.42	12	0.81	20.59	5075	35.00	3.50	89.0	23200	160.00	B2 0.36

No Fittings Found