



AIR 400

Continental Hand-Built Air Hoses – Rugged, Reliable, and Ready for Anything. For industrial professionals who demand more than just a basic air hose, Continental’s hand-built series—delivers unmatched durability and performance. Designed for rough industrial environments, mines, quarries, and construction sites, these hoses are built to withstand the harshest conditions.

Performance + Specs

Tube • SBR Rubber • Non-Conductive	Cover • SBR Rubber
Reinforcement • Spiral-Plied Synthetic Fabric	Temperature Range • -25°F / -32°C ~ 180°F / 82°C
Design Factor • 4:1	Packaging • Coiled & Polywrapped
Coupling • Contact fitting manufacturer for proper fitting recommendation and coupling procedure.	

Branding

CONTINENTAL AIR 400 PSI MAX WP MADE IN CANADA

Air 400

Order Codes: 549-006 (Green 1/2"-6"), 541-006 (3-3/4"-8")

Product Numbers

ID (in)	ID (mm)	Nom. OD (in.)	Nom. OD (mm)	Length (ft)	Color	Min. Burst (PSI)	Min. Burst (Mpa)	WP (PSI)	WP (MPa)	Weight (lbs/ft)	Weight (kg/m)	Part Number
1/2	12.70	0.88	22.26	50	Green	1600	11.03	400	2.76	0.25	0.37	20018817
				100	Green	1600	11.03	400	2.76	0.25	0.37	20018818
3/4	19.05	1.14	29.05	100	Green	1600	11.03	400	2.76	0.35	0.52	20018820
				400	Green	1600	11.03	400	2.76	0.35	0.52	20066456
1	25.40	1.53	38.92	50	Green	1600	11.03	400	2.76	0.63	0.94	20018822
				100	Green	1600	11.03	400	2.76	0.63	0.94	20018823
				400	Green	1600	11.03	400	2.76	0.63	0.94	20160501
				400	Green	1600	11.03	400	2.76	0.63	0.94	20018824
1-1/4	31.75	1.78	45.27	2	Green	1600	11.03	400	2.76	148.89	221.57	20418962
				100	Green	1600	11.03	400	2.76	0.76	1.13	20018826
				200	Green	1600	11.03	400	2.76	0.76	1.13	20159322
				400	Green	1600	11.03	400	2.76	0.76	1.13	20025018
1-1/2	38.10	2.07	52.50	2	Green	1600	11.03	400	2.76	185.78	276.47	20418963
				50	Green	1600	11.03	400	2.76	0.94	1.40	20018827
				100	Green	1600	11.03	400	2.76	0.94	1.40	20018828
				400	Green	1600	11.03	400	2.76	0.94	1.40	20025019
				400	Green	1600	11.03	400	2.76	0.94	1.40	20160502
1-3/4	45.08	2.34	59.48	196.83	Green	1600	11.03	400	2.76	214.21	318.78	20419190
				400	Green	1600	11.03	400	2.76	1.09	1.62	21030163
2	50.80	2.59	65.76	2	Green	1600	11.03	400	2.76	247.53	368.37	20418964
				100	Green	1600	11.03	400	2.76	1.26	1.87	20018830
				200	Green	1600	11.03	400	2.76	1.26	1.87	20030063
				400	Green	1600	11.03	400	2.76	1.26	1.87	20105465
2-1/4	57.15	2.87	72.83	400	Green	1600	11.03	400	2.76	1.48	2.21	21030164
2-1/2	63.50	3.12	79.18	2	Green	1600	11.03	400	2.76	321.05	477.77	20418965
				400	Green	1600	11.03	400	2.76	1.63	2.43	20195764
				400	Green	1600	11.03	400	2.76	1.63	2.43	20176780
3	76.20	3.62	91.88	2	Green	1600	11.03	400	2.76	378.04	562.59	20418967
				100	Green	1600	11.03	400	2.76	1.92	2.86	20018832
				400	Green	1600	11.03	400	2.76	1.92	2.86	20018834
3-1/8	79.40	3.77	95.88	400	Green	1600	11.03	400	2.76	2.11	3.14	20594222
3-3/4	95.38	4.42	112.34	100	Green	1600	11.03	400	2.76	2.55	3.79	21156812
4	101.60	4.67	118.56	2	Green	1600	11.03	400	2.76	531.29	790.65	20419191
				100	Green	1600	11.03	400	2.76	2.70	4.02	20728555
				400	Green	1600	11.03	400	2.76	2.70	4.02	21108315
5	127.00	5.78	146.92	2	Green	1600	11.03	400	2.76	779.22	1,159.61	20419192
6	152.40	6.81	173.04	2	Green	1600	11.03	400	2.76	949.53	1,413.06	20419193
6	152.40	6.61	168.00	100	Green	1600	11.03	150	1.03	3.61	5.38	20308295
8	203.40	8.59	218.12	100	Green	1600	11.03	100	0.69	4.50	6.69	20240195