



## ALLCRETE® TEXTILE

Allcrete™ Textile Hose is ideal for the transfer of plaster, grout, and shotcrete. Designed to handle a wide range of materials pumped to concrete structures, dams, tunnel faces, swimming pools, and more, it serves as a flexible, durable connection between pumping equipment and hard piping. Exceeds ASME B30.27-2019 standards for material placement systems. 2:1 working pressure to burst pressure ratio for enhanced safety and reliability.

### Performance + Specs

|                                                                                                                             |                                                                                                                                                                                                                    |
|-----------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Tube</b>                                                                                                                 | <b>Cover</b>                                                                                                                                                                                                       |
| <ul style="list-style-type: none"> <li>Chemituf®</li> </ul>                                                                 | <ul style="list-style-type: none"> <li>SBR</li> </ul>                                                                                                                                                              |
| <b>Reinforcement</b>                                                                                                        | <b>Temperature Range</b>                                                                                                                                                                                           |
| <ul style="list-style-type: none"> <li>Spiral-Plied High-Strength Fabric</li> </ul>                                         | <ul style="list-style-type: none"> <li>-25°F / -32°C ~ 180°F / 82°C</li> </ul>                                                                                                                                     |
| <b>Packaging</b>                                                                                                            | <b>Coupling</b>                                                                                                                                                                                                    |
| <ul style="list-style-type: none"> <li>- 50ft Lengths, Coiled &amp; Poly-Wrapped</li> </ul>                                 | <ul style="list-style-type: none"> <li>Refer to Continental Assembly manual or contact fitting manufacture for proper fitting recommendations and copuling procedures. Factory assemblies are available</li> </ul> |
| <b>Non Stock / Sizes</b>                                                                                                    |                                                                                                                                                                                                                    |
| <ul style="list-style-type: none"> <li>For special production run minimum requirements, Contact Customer Service</li> </ul> |                                                                                                                                                                                                                    |

### Branding

Allcrete® Textile Ply Plaster, Grout Concrete ContiTech 2" 1233 PSI / 85 Bar WP Weight filled with concrete (150 lbs/ft³). Exceeds ASME B30.27-2019

**Allcrete® Textile Chemituf®**

**Order Codes:** 549-638

### Product Numbers

| ID (in) | ID (mm) | Nom. OD (in.) | Nom. OD (mm) | Length (ft) | Color | Min. Burst (PSI) | Min. Burst (Mpa) | WP (PSI) | WP (MPa) | Weight (lbs/ft) | Weight (kg/m) | Part Number     |
|---------|---------|---------------|--------------|-------------|-------|------------------|------------------|----------|----------|-----------------|---------------|-----------------|
| 1       | 25.40   | 1.66          | 42.28        | 50          | Black | 4932             | 34.00            | 1233     | 8.5      | 0.72            | 1.07          | <b>20019933</b> |
|         |         |               |              | 100         | Black | 4932             | 34.00            | 1233     | 8.5      | 0.72            | 1.07          | <b>20019934</b> |
|         |         |               |              | 400         | Black | 4932             | 34.00            | 1233     | 8.5      | 0.72            | 1.07          | <b>20019935</b> |
| 1-1/4   | 31.75   | 1.91          | 48.63        | 50          | Black | 4932             | 34.00            | 1233     | 8.5      | 0.86            | 1.28          | <b>20019937</b> |
| 1-1/2   | 38.10   | 2.30          | 58.42        | 50          | Black | 4932             | 34.00            | 1233     | 8.5      | 1.24            | 1.84          | <b>20019941</b> |
|         |         |               |              | 100         | Black | 4932             | 34.00            | 1233     | 8.5      | 1.24            | 1.84          | <b>20019942</b> |
| 2       | 50.80   | 2.80          | 71.12        | 50          | Black | 4932             | 34.00            | 1233     | 8.5      | 1.56            | 2.32          | <b>20019945</b> |
|         |         |               |              | 100         | Black | 4932             | 34.00            | 1233     | 8.5      | 1.56            | 2.32          | <b>20019947</b> |
| 2-1/2   | 63.50   | 3.36          | 85.42        | 50          | Black | 4932             | 34.00            | 1233     | 8.5      | 2.05            | 3.05          | <b>20019959</b> |
|         |         |               |              | 100         | Black | 4932             | 34.00            | 1233     | 8.5      | 2.05            | 3.05          | <b>20019960</b> |
|         |         |               |              | 400         | Black | 4932             | 34.00            | 1233     | 8.5      | 2.05            | 3.05          | <b>20019961</b> |
| 3       | 76.20   | 3.94          | 100.04       | 50          | Black | 4932             | 34.00            | 1233     | 8.5      | 2.64            | 3.92          | <b>20019964</b> |
|         |         |               |              | 100         | Black | 4932             | 34.00            | 1233     | 8.5      | 2.64            | 3.92          | <b>20019965</b> |
| 3-1/2   | 89.92   | 4.48          | 113.76       | 50          | Black | 4932             | 34.00            | 1233     | 8.5      | 3.04            | 4.53          | <b>20019967</b> |
|         |         |               |              | 100         | Black | 4932             | 34.00            | 1233     | 8.5      | 3.04            | 4.53          | <b>20019968</b> |
| 4       | 101.60  | 4.94          | 125.44       | 50          | Black | 4932             | 34.00            | 1233     | 8.5      | 3.39            | 5.05          | <b>20019970</b> |
|         |         |               |              | 100         | Black | 4932             | 34.00            | 1233     | 8.5      | 3.39            | 5.05          | <b>20019971</b> |

## Allcrete® Textile ContiClean Survivor

Order Codes: 549-802 (ContiClean Survivor)

### Product Numbers

| ID<br>(in) | ID<br>(mm) | Nom. OD<br>(in.) | Nom. OD<br>(mm) | Length<br>(ft) | Color | Min. Burst<br>(PSI) | Min. Burst<br>(Mpa) | Vacuum<br>(in.) | Vacuum<br>(mm) | WP<br>(PSI) | WP<br>(MPa) | Weight<br>(lbs/ft) | Weight<br>(kg/m) | Part<br>Number  |
|------------|------------|------------------|-----------------|----------------|-------|---------------------|---------------------|-----------------|----------------|-------------|-------------|--------------------|------------------|-----------------|
| 1-1/2      | 38.10      | 2.30             | 58.42           | 50             | Black | 4932                | 34.00               | 29.00           | 736.60         | 1233        | 8.5         | 1.21               | 1.80             | <b>20673536</b> |
| 2          | 50.80      | 2.80             | 71.12           | 100            | Black | 4932                | 34.00               | 29.00           | 736.60         | 1233        | 8.5         | 1.53               | 2.28             | <b>20673538</b> |
| 2-1/2      | 63.50      | 3.36             | 85.42           | 100            | Black | 4932                | 34.00               | 29.00           | 736.60         | 1233        | 8.5         | 2.00               | 2.98             | <b>20805003</b> |
| 3          | 76.20      | 3.94             | 100.04          | 100            | Black | 4932                | 34.00               | 29.00           | 736.60         | 1233        | 8.5         | 2.58               | 3.84             | <b>20805006</b> |
| 3-1/2      | 89.92      | 4.48             | 113.76          | 100            | Black | 4932                | 34.00               | 29.00           | 736.60         | 1233        | 8.5         | 2.98               | 4.44             | <b>20805008</b> |
| 4          | 101.60     | 4.94             | 125.44          | 100            | Black | 4932                | 34.00               | 29.00           | 736.60         | 1233        | 8.5         | 3.32               | 4.94             | <b>20805020</b> |

## Allcrete® Textile Styrene-Butadiene (SBR), Butadiene (BR), Natural Rubber (NR)

Order Codes: 541-638 5" ID >

### Product Numbers

| ID<br>(in) | ID<br>(mm) | Nom. OD<br>(in.) | Nom. OD<br>(mm) | Length<br>(ft) | Color | Min. Burst<br>(PSI) | Min. Burst<br>(Mpa) | WP<br>(PSI) | WP<br>(MPa) | Weight<br>(lbs/ft) | Weight<br>(kg/m) | Part<br>Number  |
|------------|------------|------------------|-----------------|----------------|-------|---------------------|---------------------|-------------|-------------|--------------------|------------------|-----------------|
| 5          | 127.00     | 6.05             | 153.56          | 100            | Black | 4932                | 34.00               | 1233        | 8.5         | 4.66               | 6.94             | <b>20164566</b> |
| 6          | 152.40     | 7.12             | 180.80          | 50             | Black | 4932                | 34.00               | 1233        | 8.5         | 5.92               | 8.81             | <b>20392998</b> |