



ALLCRETE® WIRE

For handling wet concrete with high head pressures at the critical flex areas of a concrete boom truck and as a discharge hose on the delivery end of high-pressure concrete pumps. Exceeds ASME B30.27-2019. 2:1 WP to burst ratio.

Performance + Specs

Tube

- ContiClean Survivor®

Cover

- SBR

Reinforcement

- Spiral-Plied Steel Wire

Temperature Range

- 40°F / -40°C ~ 180°F / 82°C

Packaging

- Coiled & Poly-Wrapped

Coupling

- Refer to Continental Assembly manual or contact fitting manufacture for proper fitting recommendations and coupling procedures.

Non Stock / Sizes

- For special production run minimum requirements, Contact Customer Service.

Branding

Allcrete® Steel Reinforced Concrete Hose ContiTech 3" ID 1233 PSI / 85 Bar WP. Weight filled with concrete (150 lbs./ft.3). Exceeds ASME B30.27-2019

Allcrete® Wire

Order Codes: 541-670 (Chemituf 2-1/2"-6"), 549-670 (Chemituf 2"-5"), 549-881 (Survivor®)

Product Numbers

ID (in)	ID (mm)	Nom. OD (in.)	Nom. OD (mm)	Length (ft)	Color	Min. Burst (PSI)	Min. Burst (Mpa)	WP (PSI)	WP (MPa)	Weight (lbs/ft)	Weight (kg/m)	Part Number
2	50.80	2.99	76.00	100	Black	2466	17.00	1233	8.5	2.74	4.07	20032690
2-1/2	63.50	3.49	88.70	100	Black	2466	17.00	1233	8.5	3.28	4.88	20672114
3	76.20	3.99	101.40	50	Black	2466	17.00	1233	8.5	3.82	5.68	20020019
				100	Black	2466	17.00	1233	8.5	3.82	5.68	20674835
4	101.60	4.99	126.80	50	Black	2466	17.00	1233	8.5	4.90	7.30	20020022
				100	Black	2466	17.00	1233	8.5	4.90	7.30	20864709
				100	Black	2466	17.00	1233	8.5	4.83	7.19	21229944
5	127.00	5.99	152.20	100	Black	2466	17.00	1233	8.5	5.99	8.91	20864821
				200	Black	2466	17.00	1233	8.5	5.90	8.78	20833996
6	152.40	7.26	184.40	100	Black	2466	17.00	1233	8.5	9.60	14.28	20910862