



ARCTIC FLEXWING®

Arctic Flexwing® is for use in low-temperature operations for transferring gasoline, oil and other petroleum products.

Performance + Specs

Tube

- Ultra-low Temperature Oil Resistant Synthetic Rubber
- ARPM Class A (High Oil Resistance)

Cover

- Ultra-Low Temperature Synthetic Rubber
- Wrapped Finish

Reinforcement

- Spiral-plied Synthetic Fabric
- with Wire Helix

Temperature Range

- -65°F / -54°C ~ 180°F / 82°C

Design Factor

- 4:1

Packaging

- 100ft; Coiled & Poly-Wrapped

Coupling

- Refer to the Continental Industrial Hose Assembly Manual for crimp specifications.

Downloads

- [Alternative Fuel Compatibility \(Tubes & Covers\)](#)

Branding

CONTINENTAL ARCTIC FLEXWING 150 PSI WP CAUTION: MADE IN CANADA

Arctic Flexwing®

Order Codes: 543-650

Product Numbers

ID (in)	ID (mm)	Nom. OD (in.)	Nom. OD (mm)	Length (ft)	Color	Min. Burst (PSI)	Min. Burst (Mpa)	Bend Radius (in.)	Bend Radius (mm)	Vacuum (in.)	Vacuum (mm)	WP (PSI)	WP (MPa)	Weight (lbs/ft)	Weight (kg/m)	Part Number
1	25.40	1.48	37.70	100	Blue	600	4.14	2.50	63.50	29.00	736.60	150	1.03	0.58	0.86	20017995
1-1/4	31.75	1.73	44.00	100	Blue	600	4.14	3.00	76.20	29.00	736.60	150	1.03	0.70	1.03	20017996
1-1/2	38.10	2.05	52.00	100	Blue	600	4.14	4.00	101.60	29.00	736.60	150	1.03	0.95	1.41	20017997
2	50.80	2.55	64.70	100	Blue	600	4.14	5.00	127.00	29.00	736.60	150	1.03	1.22	1.81	20018001
				400	Blue	600	4.14	5.00	127.00	29.00	736.60	150	1.03	1.22	1.81	20265745
2-1/2	63.50	3.14	79.63	100	Blue	600	4.14	6.00	152.40	29.00	736.60	150	1.03	1.78	2.65	20018002
3	76.20	3.64	92.33	100	Blue	600	4.14	8.00	203.20	29.00	736.60	150	1.03	2.10	3.12	20018004
4	101.60	4.73	120.02	100	Blue	600	4.14	12.00	304.80	29.00	736.60	150	1.03	3.14	4.67	20018005
6	152.40	6.85	174.00	100	Blue	600	4.14	24.00	609.60	29.00	736.60	150	1.03	5.71	8.50	20018007