

## ARCTIC ORTAC™ PLUS

A low-temperature hose construction for air, water, oil, fuel oil and some chemical operations where temperatures fall as low as -65°F (-54°C).

### Performance + Specs

|                                                                                                                                                          |                                                                                                                                                       |
|----------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Tube</b> <ul style="list-style-type: none"> <li>Synthetic Rubber</li> </ul>                                                                           | <b>Cover</b> <ul style="list-style-type: none"> <li>Synthetic Rubber</li> </ul>                                                                       |
| <b>Reinforcement</b> <ul style="list-style-type: none"> <li>1 Layer; Braided; Textile</li> <li>Static wire</li> </ul>                                    | <b>Temperature Range</b> <ul style="list-style-type: none"> <li>-65°F / -54°C ~ 180°F / 82°C</li> </ul>                                               |
| <b>Design Factor</b> <ul style="list-style-type: none"> <li>4:1</li> </ul>                                                                               | <b>Packaging</b> <ul style="list-style-type: none"> <li>500ft reels, maximum 3 pieces, 50ft minimum length</li> </ul>                                 |
| <b>Coupling</b> <ul style="list-style-type: none"> <li>Contact fitting manufacturer for proper fitting recommendation and coupling procedure.</li> </ul> | <b>Non Stock / Sizes</b> <ul style="list-style-type: none"> <li>For special production run minimum requirements, Contact Customer Service.</li> </ul> |

### Branding

Continental 9.5mm 3/8" Arctic Ortac® Plus 2.1 MPA/300 PSI. Made In USA

#### Arctic Ortac™ Plus

**Order Codes:** 536-275 (Blue)

### Product Numbers

| ID (in) | ID (mm) | Nom. OD (in.) | Nom. OD (mm) | Length (ft) | Color | Min. Burst (PSI) | Min. Burst (Mpa) | Bend Radius (in.) | Bend Radius (mm) | WP (PSI) | WP (MPa) | Weight (lbs/ft) | Weight (kg/m) | Part Number |
|---------|---------|---------------|--------------|-------------|-------|------------------|------------------|-------------------|------------------|----------|----------|-----------------|---------------|-------------|
| 3/4     | 19.10   | 1.18          | 29.97        | 500         | Blue  | 1200             | 8.27             | 9.00              | 228.60           | 300      | 2.07     | 0.41            | 0.61          | 20159304    |
| 1       | 25.40   | 1.50          | 38.10        | 500         | Blue  | 1200             | 8.27             | 12.00             | 304.80           | 300      | 2.07     | 0.61            | 0.91          | 20146766    |