



AUGER ARC PILING

For use in handling a multitude of materials being pumped to concrete forms and structures.

Performance + Specs

Tube Chemituf®	Cover Black SBR with gray abrasion resistant spiral strip
Reinforcement 6 Fabric Plies with Boot Straps	Temperature Range -35°F / -37°C ~ 180°F / 82°C
Design Factor 4:1	Packaging Coiled & Poly-Wrapped
Coupling Contact fitting manufacturer for proper fitting recommendation and coupling procedure.	Non Stock / Sizes For special production run minimum requirements, Contact Customer Service.

Branding

CONTINENTAL AUGER ARC PILING HOSE MADE IN CANADA

Auger Arc Piling

Order Codes: 549-815

Product Numbers

ID (in)	ID (mm)	Nom. OD (in.)	Nom. OD (mm)	Length (ft)	Color	Min. Burst (PSI)	Min. Burst (Mpa)	WP (PSI)	WP (MPa)	Weight (lbs/ft)	Weight (kg/m)	Part Number
1-1/2	38.10	2.41	61.25	200	Black			1000	6.89	1.44	2.14	20134577
2-1/2	63.50	3.49	88.52	50	Black	3200	22.06	800	5.52	2.36	3.52	20032406
3	76.20	4.03	102.31	50	Black	3200	22.06	800	5.52	2.88	4.29	20032476